

# HOSE REELS

Quick Reference Guide

Air | Water | Oil | Diesel | Grease



# HOSE REELS

## Koreel Air Floor Reel



90-KRA-1130B	
Hose ID	Length
11mm	30m

**Use:** Various workshops, construction sites and contractors, running medium to large air tools over a long distance

**Feature:** Portable, spring rewind, strong frame, flexible PU hose, 10Bar working pressure

**Construction:** Steel body powder coated in yellow, roller guide to protect hose during use

## Koreel Air Reel Manual



90-KPM-830R	
Hose ID	Length
8mm	30m

**Use:** Various workshops, perfect for builders and contractors who require a manual hose reel for use on site. Perfect way to keep your hose tidy

**Feature:** Swiveling, lightweight manual rewinding, portable, flexible PU hose, 10Bar working pressure

**Installation:** Mobile vehicles

**Construction:** The reel body is steel powder coated in red, with a steel frame powder coated in black mounted on a swivel base

## Koreel Air Reel



90-KRA-815N	
Hose ID	Length
8mm	15m

90-KRA-825N	
Hose ID	Length
8mm	25m

90-KRA-1115N	
Hose ID	Length
11mm	15m

**Use:** Various workshops, perfect for use with small to medium air tools, mobile service vehicles

**Feature:** Lightweight, flexible PU hose, easy to install, spring rewind, 10Bar working pressure

**Installation:** Wall (within 4m height), ceiling

**Construction:** Steel body powder coated in yellow, roller guide to protect hose during use

## Ecodora Stainless Steel Air/Water Reel



90-433/22	
Hose ID	Length
13mm	15m

90-533/22	
Hose ID	Length
13mm	25m

90-543/22	
Hose ID	Length
19mm	25m

90-E544/20	
Hose ID	Capacity
25mm	No Hose

**Use:** Corrosive Environments, Manufacturing Plants, Commercial Kitchens, Marine, Hygienic Environments, Food Processing, Wash-down

**Feature:** Strong stainless steel frame, High tension spring rewind, stainless swivel joint, viton seals, rated to 100Bar, rubber non-marking hose

**Installation:** Floor, wall (within 4m height), ceiling

**Construction:** Heavy gauge 304 Stainless Steel body, roller guide to protect hose during use

## Koreel Air / Water Reel



Also available in 30m versions

**Use:** Food industry, construction site, various industrial workshops, mounted onto vehicles, suitable for water or air so can be used on large airtools

**Feature:** Strong frame, spring rewind, heavy duty PVC hose, 15Bar working pressure

**Installation:** Floor, wall (within 2m height)

**Construction:** Steel body powder coated in yellow, roller guide to protect hose during use

90-KRWA-1315	
Hose ID	Length
13mm	15m

90-KRWA-1915	
Hose ID	Length
19mm	15m

90-KRWA-2515	
Hose ID	Length
25mm	15m

90-KRWA-1920	
Hose ID	Length
19mm	20m

90-KRWA-2520	
Hose ID	Length
25mm	20m

## Koreel Stainless Steel Air/Water Reel



90-KRWA-1920SUS	
Hose ID	Length
19mm	20m

90-KRWA-2520SUS	
Hose ID	Length
25mm	20m

**Use:** Corrosive Environments, Manufacturing Plants, Commercial Kitchens, Marine, Hygienic Environments, Food Processing, Food Grade Wash-down

**Feature:** Strong stainless steel frame, spring rewind, heavy duty PVC hose, 15Bar working pressure

**Installation:** Floor, wall (within 2m height)

**Construction:** Heavy gauge 304 Stainless Steel body, roller guide to protect hose during use



# HOSE REELS

## Piusi Diesel Hose Reel



Also available in gasoline version and without hose

90-F0075003B	
Hose ID	Length
25mm	10m
94-F0075010B	
Hose ID	Length
19mm	14m
94-F0075019B	
Hose ID	Length
25mm	15m

**Use:** Designed to ensure high efficiency diesel transfer. Sturdy structure guarantees best performance in heavy duty conditions

**Feature:** Flexible rubber hose, reduced pressure loss, Easy and versatile installation, and adjustable arm positions, 10Bar working pressure, spring rewind

**Construction:** Steel powder-coated black structure, corrosion resistant, hose stop, protective side covers

## Piusi Grease Reel



94-HA40151400A	
Hose ID	Length
6.4mm	15m
94-HA40153800A	
Hose ID	Length
10mm	15m

**Use:** Various workshops, vehicle service centres, mobile fleet servicing

**Feature:** Flexible rubber hose, spring rewind, 400 Bar working pressure

**Installation:** Floor, Wall (within 4m height) or ceiling

**Construction:** Steel body powder coated in black, roller guide to protect hose during use

**Extras:** Safety covers and rotating wall brackets are available

## Geco Reels



90-5***	
Size	Length
10 to 25mm	No Hose

Ranges from 10mm to 25mm and hose length from 15m to 100m

Does not include hose

**Use:** Various workshops, mobile fleet servicing, water blast, agriculture

**Feature:** Brass swivel, up to 52Bar working pressure. Manual reel, mini, maxi, mini mega and mega options available

**Installation:** Floor, mobile vehicles

**Construction:** welded steel construction, zinc plated and powder coated.

**Extras:** Stainless hi-pressure swivels up to 276Bar

## Piusi Air / Water Reel



90-HA20153800A	
Hose ID	Length
10mm	15m

Safety covers and rotating wall brackets available

**Use:** Various workshops, industrial applications, vehicle service centres. Perfect for use with air tools or water

**Feature:** Lightweight flexible rubber hose, easy to install, kink guard, 20Bar working pressure, spring rewind

**Installation:** Floor, wall (within 4m height) or ceiling

**Construction:** Steel body powder coated in black. Roller guide to protect hose during use

## Piusi Oil Reel



94-HA6015120B	
Hose ID	Length
13mm	15m
94-HA6010120B	
Hose ID	Length
13mm	10m

**Use:** Various workshops, oil installations, vehicle service centres

**Feature:** Light weight flexible rubber hose, easy to install, 60 Bar working pressure, spring rewind

**Installation:** Floor, wall (within 4m height) or ceiling

**Construction:** Steel body powder coated in black, roller guide to protect hose during use

**Extras:** Safety covers and rotating wall brackets are available

## Ecodora Manual Hose Reels



90-74305/10	
13mm x 17m	
90-75300/10	
13mm x 25m	
90-75400/10	
25mm x 15m	
90-75600/10	
25mm x 30m	



90-OE7522001/100	
25mm x 20m	
90-OE7532001/100	
25mm x 30m	
90-OE7552001/100	
25mm x 50m	
90-OE7562001/100	
25mm x 70m	

Does not include hose

**Use:** Variety of industrial applications, air, water, oil & diesel

**Feature:** Up to 20Bar working pressure. Manual reel, heavy duty Italian quality

**Installation:** Floor, wall, mobile vehicles

**Construction:** Painted steel, viton seals, brass swivel

# HOSE REELS

## RAASM Cable Reel 230V 15m



90-2315SFA	
Hose ID	Length
10mm	15 m

**Use:** Various workshops

**Feature:** 230V Single phase, IP44 electrical protection, can operate in -5°C to 40°C temperatures, thermal protector. 0.9kW max power use at 20°C when wound, 1.4kW max power use at 20°C when unwound

**Construction:** 2x1-H05 VV-F cable type, 14+1m cable length, 1.2m cable inlet.

## Koreel Water Blast Reel



90-KRWA0930R2H	
Hose ID	Length
10mm	30m

90-KRWA0930R2HS <small>Stainless Steel</small>	
Hose ID	Length
10mm	30m

90-KRWA-915H2-ST	
Hose ID	Length
10mm	15m

**Use:** Food industry, Construction site, Various industrial workshops, mounted onto vehicles

**Feature:** Strong frame, spring rewind, 2 wire rubber hose, 276Bar working pressure

**Installation:** Floor, Wall (within 4m height)

**Construction:** Steel body powder coated in yellow, roller guide to protect hose during use

## Retracta Air/Water Hose Reel



C1AW315B-01C	
Hose ID	Length
10mm	15m

C1AW412B-01CC	
Hose ID	Length
12mm	12m

**Use:** Ideal for small spaces

**Feature:** 35% smaller than R3 series, UV stabilised & resistant poly case, 3 position reel swivel locking, bend restricter, 17Bar working pressure

**Installation:** Wall

**Construction:** 180° swivel bracket, powder coated steel bracket, hybrid polymer hose

## Ecodora Water Blast Reel



90-430/39	
Hose ID	Length
10mm	15m

**Use:** Food industry, Construction site, Various industrial workshops, mounted onto vehicles

**Feature:** Strong frame, High tension spring, 2 wire rubber hose, 400Bar working pressure, max temperature 130°C

**Installation:** Floor, Wall (within 4m height)

**Construction:** Steel body powder coated in yellow, roller guide to protect hose during use

## Koreel Twinline Welding Reel



90-KRGA-615N	
Hose ID	Length
6mm	15m

**Use:** Gas welding, cutting

**Feature:** Flexible rubber hose, spring rewind, 10Bar working pressure

**Installation:** Floor, wall (within 3m height)

**Construction:** Steel body powder coated in yellow, roller guide to protect hose during use

## Piusi Suzzara AdBlue Reel



94-F0075011B	
Hose ID	Length
20mm	15m

**Use:** Various workshops, vehicle service centres, mobile fleet servicing

**Feature:** Flexible rubber hose, spring rewind, adjustable arms, 10 Bar working pressure, designed for DEF fluid

**Installation:** Floor, Wall (within 4m height) or ceiling

**Construction:** All components are compatible with Urea to avoid corrosion, roller guide to protect hose during use



Find a location near you!

Scan the QR Code or visit [motionfluid.co.nz](http://motionfluid.co.nz)

0800 4 HOSES

**MiMOTION**  
FLUID POWER SOLUTIONS